


LL1D4D-S Limit Switch 行程开关




保护构造 protection degree		IP65(EN60947-5-1)
寿命 life	机械性mechanical	100万次以上
	电气性electrical	15万次以上(AC250V 10A阻抗负载)
容许操作速度 operation speed		0.1m/s~0.5m/s
接点间隙 (contactor gap)		最小2×2mm
容许操作频率 operation frequency		最大30次/min
强制开离力 force strength		最小58.84N(6kgf)
强制开离行程 force movement		最小10mm
绝缘阻抗 Isulation resistance		同极端子间和各端子及非充电金属部间 between terminal of same pole, every terminals, and non-charged metal parts > 100MΩ
接触电阻 contact resistance		25MΩ以下(初期值)
耐电压 voltage withstand	同极端子间 same terminal	Uiimp 4KV(EN60947-5-1)
	共极端子间 terminal in same pole	Uiimp 4KV(EN60947-5-1)
	各端子和非充电金属部间 terminal and non-charged metal	Uiimp 4KV(EN60947-5-1)
额定绝缘电压 (U _i) rated isolation voltage		400V max.(EN60947-5-1)
附带条件短路电流 proviso short circuit current		100A(EN60947-5-1)
闭路时逆起电压 completed-circuit opposite voltage		最大1,500V(EN60947-5-1)
污染度(使用环境)dustiness		污染度3(EN60947-5-1)
额定密闭热电流 (thermocurrent) rated obturated thermocurrent		10A(EN60947-5-1)
感电保护等级 electrification protection degree		Class II (双重绝缘double insulation)
振动 vibration	误动作 misoperation	10~55Hz 单振幅amplitude 0.75mm
冲击 impact	耐久 endurance	1,000m/s ² [100G以上]
	误动作 misoperation	300m/s ² [30G以上]
使用周围温度 temperature		-30~+70°C(但不能结冰with no ice)
使用周围湿度 humidity		< 95%RH

型式 mode	LL1D4DS-1□□S型	LL1D4DS-5□□S型
动作特性 operation specialty	LL1D4DS-2□□S型	LL1D4DS-6□□S型
操作KEY插入力量 insert strength	最大 14.71N(1.500gf)	14.71N(1.500gf)
操作KEY拔出力量 pluck out strength	最大 29.42N(3,000gf)	29.42N(3,000gf)
动作前移动 move before operation	6 ± 3mm	6 ± 3mm
整体移动 move as a whole	28mm	28mm
强制开离力 force strength 最小 强制开离冲程 force movement 最小	58.84N(6,000gf) 10mm	58.84N(6,000gf) 10mm

接触形式 Contact Type



一开一闭型
1NC+1NO Type



二闭型
2NC Type

LL1D4DS-□□□□型
1 2 3 4

1尺寸 dimension

Pg13.5(出线孔型wire hole type)

G1/2(出线孔型wire hole type)

1/2~14NPT(wire hole type)

Pg13.5(wire hole type)

G1/2(wire hole type)

F: 正面 face

4头部型式 head type

S: 标准 standard

2内藏开关 inside switch
1NC.1NO接点contact(Slow Action)
2NC接点contact(Slow Action)
3头部安装方向 the position of head install
F: 正面 face
4头部型式 head type
S: 标准 standard

